

## Agasthya 2013 Series Trace Oxygen Analyzer Model Bhoomi 330



### Features:

- 32-Bit Cortex-M3 ARM Processor
- Long life Paramagnetic O<sub>2</sub> sensor
- RS 485, supports MODBUS protocol
- PTFE tubing and corrosion-resistant components for internal sample health
- Flow meter for flow regulation

## Agasthya 2013 Series Trace Oxygen Analyzer Model Bhoomi 330

### Specification

Method of Detection	: Paramagnetic sensor for O <sub>2</sub>
Range Available	: 0-30% scalable
Resolution	: 0.01%
Accuracy & Repeatability	: ± 1% of FS
Drift	: <2% of full scale per month
Response Time (T-90)	: ≤30 seconds
Display	: Touch Screen LCD LED
Power	: 80 to 230 VAC 50 Hz
Power Consumption	: 8 Watts
Digital Output	: RS485 with MODBUS Protocol
Analog Output	: 4-20 mA (max load resistance upto 500 Ω)
Relay Output	: 2 nos. of potential free contacts
Humidity	: 5-95% RH
Ambient Temperature Range	: 4 to 50°C
Flow Meter	: 0.1-1 LPM
Enclosure	: Wall, Panel, Rack & Table Top
Sample Connection	: 1/4 inch S.S. Connection
Area Classification	: General Purpose

### Ordering Code

Basic Model	Technology	Measurement Units	Enclosure Type	Display
330	PAR – Paramagnetic	%	W - Wall	T - Touchscreen
			P – Panel	LCD
			R – Rack	LED
			TT – Tabletop	

#### **For Example:**

**Model No. 330-PAR-%-P-LCD**

**Trace Oxygen Analyzer Paramagnetic Sensor with % unit Panel Mount & LCD Display**

**BHOOMI**<sup>®</sup> **Process Management Pvt. Ltd.**  
(Formerly known as Bhoomi Analyzers)

#### **Head Office :**

409, 4th Floor, Avior (Nirmal Galaxy),  
Next to Deep Mandir, Opp. Johnson & Johnson,  
L.B.S. Marg, Mulund (W), Mumbai - 400080.

#### **Manufacturing Unit :**

201, 207, 208, G Wing, Udyog Bhavan No.: 2,  
Plot No.: K-3, Additional Ambarnath MIDC,  
Ambarnath-East-421506, Dist.: Thane, Maharashtra.

Phone : + 91-22-25916858, 25916916 Cell : +91 7777071509

Email : sales@bhoomiltd.com / bhoomianalyzers@gmail.com

Website : www.bhoomiltd.com