

Agasthya 2013 Series Continuous Emission Monitoring System Model BI 7000 UVDOAS



The Agasthya 2013 Series Continuous Emission Monitoring System BI 7000 UVDOAS is designed in compliance with emission norms to measure gas pollutants emitted by various process industry and to meet the needs of industries requiring cost effective and reliable multiple gas analyzer solutions.

The technology employed are of maximum reliability and accuracy to ensure high degree of performance & long life.

BI7000 is ideal solution to protect initial investment & can adapt to any process application with modular design & can house up to eight gas sensors with scalable ranges for each gas. Manufactured for use in hostile or friendly environments the BI 7000 Continuous Emission Monitoring System maintains high levels of gas selectivity. All packed into a robust, attractive, industrial enclosure.

Features

- ❖ Tried and tested technology with proven reliability
- ❖ Wide range of gas selectivity & scalable ranges available for each gas
- ❖ 5.7" TFT Keypad Display
- ❖ The best price performance on the market - designed with user requirements foremost in mind
- ❖ Isolated 4-20 mA analog output for each gas
- ❖ RS 485, supports MODBUS protocol
- ❖ High / Low Gas, low flow & other programmable events available
- ❖ Highly efficient automatic purge & drain system
- ❖ Inbuilt interface for Remote Calibration Unit
- ❖ Auto & semi auto calibration facilities

Agasthya 2013 Series Continuous Emission Monitoring System Model BI 7000 UVDOAS

Technical Specification:

Parameter	Resolution	Accuracy	Scalable Range
Hydrogen Sulphide	1 ppm	±1% FSD	0-200 ppm

Analyzer Specification:

- ❖ Repeatability : 1% FS
- ❖ Zero Drift : <±1% per week of Span
- ❖ Span Drift : <±1% per week of Span
- ❖ Response : T90 < 15 sec
- ❖ Operating Temperature : 4°C to 65°C
- ❖ Analog output : Isolated and linear 4-20mA analog output for each gas
- ❖ Digital Communication : RS 485, Supports MODBUS Protocol
- ❖ Relay Output : 2 Nos. Potential free contact for alarms
- ❖ Power Supply : 110/230 VAC, 50 Hz
- ❖ Programmable events for High / Low Alarms
- ❖ Auto & semi auto calibration facilities

System Components

- ❖ **Heated Sampling Probe**
 - Operating temperature : Max. 400°C
 - Mounting : Flange Type
 - Max. working pressure : 6 bar
 - Voltage : 110/230 V, 50 /60 Hz
 - Heating : Self regulating +180°C
 - Ambient temperature : -20 to +80°C
 - For dust concentration : Upto 5 g/m³
 - MOC : SS 316
- ❖ **Heated Sample Gas Line**
 - Process Tube : PTFE / SS
 - Process Tube Size : 1/4 inch OD
 - Heating Element : Constant watt type
 - Thermal Insulation : Non - Hygroscopic Fiber Glass
 - Outer Sheath : Extruded UV Resistant FRLS PVC
 - Operating Voltage : 230 V AC
 - Watt Density : 45 W/m
 - Length : To be specified by client
 - Max. Operating Temperature : 200°C
 - Temperature Sensor : In built RTD
 - Process Connection : Flanged Type
 - Power/Control Connection : Lead cable (3 Wire), 2 Meter for both power & control

Agasthya 2013 Series Continuous Emission Monitoring System Model BI 7000 UVDOAS

Sample Conditioning Unit

❖ Smart unit

Aspirator/Pump for sampling flue gas
Pre and post cooler fine filters to remove drain, dust and mist in sample gas
Auto drain and auto purging (blow back) facilities
2 way solenoid valves for switching, sampling, purging, draining and calibration
Flowmeter to regulate and monitor the flow of sample gas
Drain pump for continuous removal of condensate

❖ Cooler

Sample gas flow range : 1 - 3 LPM (2.1- 6.4 SCFM)
Inlet condition at rated flow : 150°C @ 12% H₂O , 2.5 LPM
Outlet dew point at rated flow : 4°C
Maximum inlet temperature : 200°C for SS
Ambient temperature range : 0.6 - 40°C
Power supply : 90 - 240 VAC, 50/60 Hz
Operating Pressure : 0.75 - 1.25 Bar w.r.t. abs

❖ Cabinet

Industrial Cabinet
Meets IP 54 standard
Inbuilt air conditioning system
Automatic cabinet illumination when door open
Earthing bar assembly
180 degree door opening
Standard Dimension : 1500 (H) x 600 (W) x 800(D) mm

BHOOMI[®] Process Management Pvt. Ltd.
(Formerly known as Bhoomi Analyzers)

Head Office :

409, 4th Floor, Avior (Nirmal Galaxy),
Next to Deep Mandir, Opp. Johnson & Johnson,
L.B.S. Marg, Mulund (W), Mumbai - 400080.

Manufacturing Unit :

201, 207, 208, G Wing, Udyog Bhavan No.: 2,
Plot No.: K-3, Additional Ambernath MIDC,
Ambernath-East-421506, Dist.: Thane, Maharashtra.

Phone : + 91-22-25916858, 25916916 Cell : +91 8652065039

Email : sales@bhoomiltd.com, service@bhoomiltd.com

Website : www.bhoomiltd.com